



GM 8L90E 14-On
1-3-5-6-7 / C3 Clutch PowerPack®
2-3-4-6-8 / C4 Clutch PowerPack®
4-5-6-7-8-Reverse / C5 Clutch PowerPack®

Instruction Sheet

Alto Kit # 224756 1-3-5-6-7 / C3 Clutch PowerPack® - GM 8L90E

Qty	Part #	Description
6	224704A164	G3® Frictions Plates (1.64mm / .065")
5	224705-203PS	Steel Plates (2.03mm / .080")
1	224705-280PS	Steel Plate (2.80mm / .111")

Alto Kit # 224757 2-3-4-6-8 / C4 Clutch PowerPack® - GM 8L90E

Qty	Part #	Description
5	224706A160	G3® Frictions Plates (1.60mm / .063")
5	224707-152PS	Steel Plates (1.52mm / .060")

Alto Kit # 224758 4-5-6-7-8-Reverse / C5 PowerPack® - GM 8L90E

Qty	Part #	Description
7	224708A165	G3® Frictions Plates (1.62mm / .064")
6	224709-203PS	Performance Steel Plates (2.03mm / .080")
1	224764C	Top Step Pressure Plate (4.92mm / .194")
1	224764B	Bottom Apply Plate (2.81mm / .111")

Installation:

1-3-5-6-7 / C3: 4 Friction Drum

The stack-up is the same as OE, you will be adding an extra friction and steel plate.

Install the 1st of 5 steel plates on top of the apply piston. Then install an internally splined friction plate, continue stacking external and internal plates ending with an internal splined friction plate, (5 internal and 5 external plates) Install pressure plate and snap ring.

1-3-5-6-7 / C3: 5 Friction Drum

The stack-up is the same as OE, you will be adding an extra friction and steel plate.

Install the 1st of 6 steel plates on top of the apply piston, the thick .111" plate. Then install an internally splined friction plate, continue stacking external and internal plates ending with an internal splined friction plate, (6 internal and 6 external plates) Install pressure plate and snap ring.

2-3-4-6-8 / C4: 4 Friction Drum

The stack-up is the same as OE, you will be adding an extra friction and steel plate.

Install the wave cushion plate against the apply piston, install the 1st of 5 steel plates on top of the wave plate. Then install an internally splined friction plate, continue stacking external and internal plates ending with an internal splined friction plate, (5 internal and 5 external plates) Install pressure plate and snap ring.

4-5-6-7-8-Reverse / C5: 5 Friction Drum

The stack-up is the same as OE, except you will eliminate the bottom wave plate, you will be adding 2 extra friction and steel plates.

Install the .111" bottom apply plate against the apply piston, install the 1st of 7 friction plates on top of the apply plate. Then install an externally splined steel plate, continue stacking internal and external plates ending with an internal splined friction plate, (7 internal friction and 6 external steel plates) Install Top 3.16 / .179" pressure plate and snap ring.

Air-check the assembly several times to seat the stack-up.

Always pre-soak the frictions in the type of ATF recommended by the OE for at least 30 minutes.

Check clutch pack clearance between the pressure plate and the snap ring in 3 different locations, clearance should be .045" to .060" (1.14 – 1.52 mm).